

ARRAY ELECTRONIC CO. LTD.

Programmable DC Electronic Loads

Model 3710A, Model 3711A

- Programmable Output
- Power Overload Protection
- Current Overload Protection
- PC Software Monitoring
- Compact and Light Weight
- Backlit LCD Display
- Can be used in a parallel connection



Specifications:	Type 3710A (\$575.00)	Type 3711A (\$775.00)
Input Voltage:	0-360V DC	0-360V DC
Input Current:	0-30A DC	0-30A DC
Input Power:	0-150W	0-300W
Voltage Accuracy:	0.000-3.999V: 0.2%+3mV 4.00-35.99V: 0.2%+30mV 36.0-360.0V: 0.2%+300mV	0.000-3.999V: 0.2%+3mV 4.00-35.99V: 0.2%+30mV 36.0-360.0V: 0.2%+300mV
Current Accuracy:	0.000-2.999A: 0.2%+3mA 3.00-30.00A: 0.2%+30mA	0.000-2.999A: 0.2%+3mA 3.00-30.00A: 0.2%+30mA
<p>Number of Inputs: 1 Minimum Resolution Voltage: 1mV, Current 1mA Lowest Conductive Resistance: <0.08Ω Ripple: <10mVpp Interface: RS232/RS485/USB Protection: Over voltage / over current / over power / over temperature / polarity-reversal Program Memory: 10 steps program, EEPROM AC Input: 110V/220V AC +/-15%, 47-63Hz Electronic load software: ActiveX and DLL tools for VB, VC++, DELPHI, LABVIEW</p> <p>Operating Environment: 0-50°C, 80% RH Weight: 5.0Kg Dimensions: 212.6mm W x 88.1mm H x 250mm D Optional Accessories: RS232 adapter, RS485 adapter, USB adapter</p>		

Electro-Meters

1-800-617-3413

website: www.electro-meters.com

Toronto

905-428-3413

email: sales@electro-meters.com

Montreal

514-336-3020

Calgary

403-462-3304

Oct 15th 2007