

CURRENT TRANSFORMERS

Model 5DRL




Window Diameter 1.56"

APPLICATION:
With ammeters, wattmeters,
cross current compensation.

FREQUENCY:
50-400 Hz.

INSULATION LEVEL:
600 Volts, 10 kV BIL full wave.

- Flexible leads are UL 1015 105 ° C, CSA approved, #16 AWG, 24" long.
- Non-standard length to be specified.
- Approximate weight: 2 lbs.



CATALOG NUMBER	CURRENT RATIO	ACCURACY AT 60 Hz	BURDEN VA at 60 Hz
5DRL-500	50:5	± 2 %	2.5
5DRL-600	60:5	± 1 %	2.5
5DRL-750	75:5	± 1 %	3.5
5DRL-101	100:5	± 1 %	5.0
5DRL-151	150:5	± 1 %	10.0
5DRL-201	200:5	± 1 %	12.5
5DRL-251	250:5	± 1 %	20.0
5DRL-301	300:5	± 1 %	25.0

CATALOG NUMBER	CURRENT RATIO	ACCURACY AT 60 Hz	BURDEN VA at 60 Hz
5DRL-401	400:5	± 1 %	40
5DRL-501	500:5	± 1 %	50
5DRL-601	600:5	± 1 %	60
5DRL-751	750:5	± 1 %	60
5DRL-801	800:5	± 1 %	60
5DRL-102	1000:5	± 1 %	75
5DRL-122	1200:5	± 1 %	90