

CURRENT TRANSFORMER

MODEL 561

Window Size 3.25" X 4.25"

APPLICATION:
Relaying and metering.
FREQUENCY:
50-400 Hz.
INSULATION LEVEL:
0.6 kV, BIL 10 kV full wave.
INSULATION SYSTEM:
Temperature Class H (180°C.)
CONTINUOUS THERMAL
RATING FACTOR:
1.33 at 30°C. amb.
1.0 at 55°C. amb.

- Terminals are brass studs No. 10-32 with one flatwasher, lockwasher and regular nut.
- Approximate weight 8 lbs.

REGULATORY AGENCY APPROVALS







E93779



LR89403

Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1



CATALOG NUMBER	CURRENT RATIO	RELAY CLASS	ANSI METERING CLASS AT 60 Hz					SECONDARY WINDING RESISTANCE (OHMS @ 75°C.)
			B0.1	B0.2	B0.5	B0.9	B1.8	
561-101	100:5	—	2.4	2.4	—	—	—	0.021
561-151	150:5	C 10	1.2	2.4	—	—	—	0.032
561-201	200:5	C 10	0.6	1.2	2.4	2.4	—	0.043
561-251	250:5	C 20	0.6	0.6	1.2	2.4	—	0.054
561-301	300:5	C 20	0.3	0.6	1.2	1.2	2.4	0.064
561-401	400:5	C 20	0.3	0.3	0.6	1.2	1.2	0.086
561-501	500:5	C 20	0.3	0.3	0.3	0.6	0.6	0.170
561-601	600:5	C 20	0.3	0.3	0.3	0.3	0.6	0.161
561-751	750:5	C 50	0.3	0.3	0.3	0.3	0.6	0.202
561-801	800:5	C 50	0.3	0.3	0.3	0.3	0.6	0.340
561-102	1000:5	C 50	0.3	0.3	0.3	0.3	0.3	0.425
561-122	1200:5	C100	0.3	0.3	0.3	0.3	0.3	0.510
561-152	1500:5	C 50	0.3	0.3	0.3	0.3	0.3	0.766
561-162	1600:5	C 50	0.3	0.3	0.3	0.3	0.3	0.817
561-202	2000:5	C100	0.3	0.3	0.3	0.3	0.3	1.021
561-252	2500:5	C100	0.3	0.3	0.3	0.3	0.3	1.276
561-302	3000:5	C 50	0.3	0.3	0.3	0.3	0.3	1.396
561-322	3200:5	C 50	0.3	0.3	0.3	0.3	0.3	1.489
561-402	4000:5	C100	0.3	0.3	0.3	0.3	0.3	1.861