

CURRENT TRANSFORMERS

Models 569TL, 569TS

Window Size 9.50" X 3.75"

APPLICATION:
Metering.

FREQUENCY:
50-400 Hz.

INSULATION LEVEL:
0.6 kV, BIL 10 kV full wave.
CONTINUOUS THERMAL
RATING FACTOR:
1.33 at 30°C. amb.
1.0 at 55°C. amb.

- TL-Terminals are brass studs No. 10-32 with one flatwasher, lockwasher and regular nut.
- TS-Terminals are brass screws No. 10-32 with one lockwasher.
- Approximate weight 5 lbs.


REGULATORY AGENCY APPROVALS






LR89403

Manufactured to meet the requirements of ANSI/IEEE C57.13.
Classified by U.L. in accordance with IEC 44-1


Model 569TL



Model 569TS



EXCITATION CURVE



CATALOG NUMBER	CURRENT RATIO	ANSI METERING CLASS AT 60 Hz					SECONDARY WINDING RESISTANCE (OHMS @ 75°C.)
		B0.1	B0.2	B0.5	B0.9	B1.8	
569**202	2000:5	0.3	0.3	0.3	0.6	0.6	0.417
569**252	2500:5	0.3	0.3	0.3	0.3	0.6	0.521
569**302	3000:5	0.3	0.3	0.3	0.3	0.6	0.625
569**322	3200:5	0.3	0.3	0.3	0.3	0.6	0.667
569**352	3500:5	0.3	0.3	0.3	0.3	0.6	0.730
569**402	4000:5	0.3	0.3	0.3	0.3	0.6	0.834
569**502	5000:5	0.3	0.3	0.3	0.3	0.6	1.042

**NOTE: When ordering, prefix Cat. No. with model designation required i.e., 569TL-201 or 569TS-201.