

# CURRENT TRANSFORMER

Model 575

Window Size 0.75" X 3.25"

## APPLICATION:

Metering.

## FREQUENCY:

50-400 Hz

## INSULATION LEVEL:

0.6 kV, BIL 10 kV full wave.

## CONTINUOUS THERMAL RATING FACTOR:

1.33 at 30°C. amb.



1.0 at 55°C. amb.

- Terminals are brass studs No. 10-32 with one flatwasher, lockwasher and regular nut.
- Approximate weight 2.5 lbs.


## REGULATORY AGENCY APPROVALS



Manufactured to meet the requirements of ANSI/IEEE C87.13.  
Classified by U.L. in accordance with IEC 44-1



EXCITATION CURVE



CATALOG NUMBER	CURRENT RATIO	ANSI METERING CLASS AT 60 Hz		SECONDARY WINDING RESISTANCE
		B0.1	B0.2	
575-101	100:5	1.2	4.8	0.010
575-151	150:5	1.2	2.4	0.018
575-201	200:5	1.2	1.2	0.033
575-251	250:5	0.6	1.2	0.045
575-301	300:5	0.6	0.6	0.056
575-401	400:5	0.6	0.6	0.078
575-501	500:5	0.6	0.6	0.098
575-601	600:5	0.6	0.6	0.117
575-801	800:5	0.3	0.3	0.157
575-102	1000:5	0.3	0.3	0.152