

CONTROL POWER TRANSFORMER

Model CPT3-60-1.5

REGULATORY AGENCY APPROVALS




APPLICATION:
To provide control power in
distribution equipment and
motor starters.

FREQUENCY:
See below




INSULATION LEVEL:
5 kV, 60 kV BIL full wave.

THERMAL RATING:
1.5 kVA at 30°C amb.


- Primary terminals are brass screws No. 10-32 with one flatwasher and lockwasher.
- Secondary terminals are brass screws 10-32 with one flatwasher and lockwasher.
- The transformer winding is vacuum encapsulated in polyurethane resin.
- Plated steel mounting base.
- For indoor use.
- Approximate weight 54 lbs.



CONNECTION DIAGRAM



(4) HOLES
0.41 DIA.



BASE PLATE

*CATALOG NO.	PRIMARY VOLTAGE	RATIO	SECONDARY VOLTAGE	FREQUENCY	PRIMARY FUSE
CPT3-60-1.5-242FF	2400V	20:1	120/240V	60Hz	3E
CPT3-60-1.5-332FF	3300V	30:1	110/220V	50Hz	2E
CPT3-60-1.5-4181FF	4160V	34.7:1	120/240V	60Hz	2E
CPT3-60-1.5-482FF	4800V	40:1	120/240V	60Hz	2E

*For fuse clips only, change FF to CC.