

CONTROL POWER TRANSFORMER

Model CPT3-60-3

REGULATORY AGENCY APPROVALS









APPLICATION:
To provide control power in distribution equipment and motor starters.

FREQUENCY:
60 Hz.

INSULATION LEVEL:
5 kV, 60 kV BIL full wave.

THERMAL RATING:
3 kVA at 30°C. amb.

- Primary terminals are brass screws No. 10-32 with one flatwasher and lockwasher or HV lead kit shown below.
- Secondary terminals are brass screws 1/4-20 with one flatwasher and lockwasher.
- The transformer winding is vacuum encapsulated in polyurethane resin.
- Plated steel mounting base.
- For indoor use.
- Approximate weight 85 lbs.




UNFUSED

FUSED

CATALOG NO.	PRIMARY VOLTAGE	RATIO	SECONDARY VOLTAGE	CATALOG NO.	PRIMARY FUSE
CPT3-60-3-242-XXX	2400	20:1	120/240	CPT3-60-3-242FF	5E
CPT3-60-3-4161-XXX	4160	34.7:1	120/240	CPT3-60-3-4161FF	3E
CPT3-60-3-482-XXX	4800	40:1	120/240	CPT3-60-3-482FF	3E

NOTE: Last three digits of (unfused) catalog number signify lead length (in inches) of HV Lead Kit.



CONNECTION DIAGRAM

