## **MODEL CA7028**

The only wire-mapper in its class with graphical and digital display of wiremap, fault type and fault location

## **SPECIFICATIONS**

OI EOII IOATIC	,110
MODEL	CA7028
MEASUREMENTS	
Range	500 ft or 150m (selectable)
Accuracy	±5% of Reading
Cable Type	UTP, STP, FTP and SSTP
Faults Indicated	Short Circuit Pair, Open Circuit Wire, Short Between Pairs,Split / Cross Pairs, Pair Reversals, Shield Continuity
<b>Fault Location</b>	Near end, remote end, or distance to fault
Fault Display	All fault and setting info displayed textually and graphically
Wiring Schemes	TIA 568A / B, USOC and ISDN
<b>Service Indication</b>	Telephone, 10BaseT, 100Mbit+, Token Ring
Voltage Warning	Audible and visual warning of TNV (Telecom Network Voltage)
Test Inhibit	Inhibits testing in the presence of live voltages
<b>Tone Generator</b>	Oscillating 810 to 1110Hz
<b>Power Source</b>	Four 1.5V AA Alkaline batteries (included)
Display Backlight	Blue electroluminescent
Remote Display	Green / Red Pass / Fail LED
Auto Power OFF	After three minutes
Weight	Main unit: 12oz (350g); Remote unit: 1.5oz (40g)



Soft carrying case, remote, (2) patch cords, (4) 1.5V AA batteries, remote unit and a user manual.







## **FEATURES**

- Hand-held LAN Cable Mapping and Troubleshooting Tester
- Indicates all common wiring faults including split pairs, shorts, opens, reversed pairs and crossed wires
- · Unique graphical and digital display of fault information and length
- Active remote unit indicates Pass/Fail at remote end by green/red LED during the test
- Indicates distances to opens and shorts and identifies location
- Display fault location up to 500 ft (150m) (selectable)
- · Built-in tone generator for tracing and locating cables
- · Built-in service check function to detect telephone, 10BaseT, 100Mbit+ and Token Ring
- Visual and audible warning of live telephone network voltages
- · Works with all category cables

Technical Assistance (800) 343-1391

- · Rugged design weighs less than 12oz (350g)
- · Large high-visibility blue electroluminescent backlit display
- Complete with remote unit and mini patch leads
- Works with TIA 568A/B, USOC and ISDN wiring schemes
- Compatible with industry standard Tone Receivers

CATALOG NO.	DESCRIPTION
2127.82	Wire Mapper Pro Model CA7028 (LAN Cable Tester)



www.aemc.com