

ARCA



















ARCA

Driven by innovation and market demand the ARCA is the ideal and cost-effective alternative to sheet steel cabinets or fiberglass enclosures needed in harsh environments.

Only Fibox offers the industry the largest UL listed, NEMA 4X polycarbonate enclosure in the world. The ARCA has the strength of a metal box and the benefits of a plastic enclosure.

Available in both landscape and portrait orientation, the ARCA cabinet series provides high impact and UV resistance. These watertight polycarbonate enclosures will not dent, crack or bloom like steel or fiberglass.

The ARCA also weighs considerably less and is easier to modify than its metal or fiberglass counterparts, saving both time and money.

The ARCA is manufactured in Fibox's Wi-Fi friendly polycarbonate, a robust, corrosion proof thermoplastic that will never rust.

Your components stay dry and dust free thanks to the formed in place PUR gasket which makes a watertight seal.

These are just a few of the reasons the ARCA is the ideal NEMA 4X cabinet enclosure for any application.

Fibox proudly offers all the standard accessories you'll need for the ARCA and can customize your selection with holes, cut-outs and recess.



UL Type 4 & 4X

IP 66

IK 10

UV - Protected

| Order S | Symbol | | Dimensions | Description |
|---------|--------|-------|------------------------------|------------------------------|
| ARCA | | NO-MP | | Opaque Hinged Lockable Cover |
| ARCA | 302015 | NO-MP | 11.81 x 7.87 x 5.9 inches | Opaque Hinged Lockable Cover |
| ARCA | 304015 | NO-MP | 11.81 x 15.75 x 5.9 inches | Opaque Hinged Lockable Cover |
| ARCA | 304021 | NO-MP | 11.81 x 15.75 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 403015 | NO-MP | 15.75 x 11.81 x 5.9 inches | Opaque Hinged Lockable Cover |
| ARCA | 403021 | NO-MP | 15.75 x 11.81 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 405021 | NO-MP | 15.75 x 19.68 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 406021 | NO-MP | 15.75 x 23.62 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 504021 | NO-MP | 19.68 x 15.75 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 507030 | NO-MP | 19.68 x 27.55 x 11.81 inches | Opaque Hinged Lockable Cover |
| ARCA | 604021 | NO-MP | 23.62 x 15.75 x 8.26 inches | Opaque Hinged Lockable Cover |
| ARCA | 608030 | NO-MP | 23.62 x 31.49 x 11.81 inches | Opaque Hinged Lockable Cover |
| ARCA | 705030 | NO-MP | 27.55 x 19.68 x 11.81 inches | Opaque Hinged Lockable Cover |
| ARCA | 806030 | NO-MP | 31.49 x 23.62 x 11.81 inches | Opaque Hinged Lockable Cover |

Mounting pods

On the base, cover and four base sides



Sloped base design

Greater water resistance

Easy assembly and refined appearance



Locking

- Double -bit
- Changeable lock inserts
- 2 point Pad-lockab' swing handle



Molded rib design

Increased strength and gasket protecti



Gasket

Oversized formed in place PUR gasket





Inner door available

- No tools needed for installation
- Lockable
- Patent pending

Corner design

Double corner allows secure mounting outside gasket area

Cover

- Front cover opens 120°
- Portrait or landscape orientation
- Door stop available







Polycarbonate:

UL Type 4 & 4X

IP 66

IK 10

UV - Protected

Customization services

All Fibox ARCA enclosures can be customized to meet your specifications. Sophisticated CNC machinery can fabricate your enclosures with holes, cutouts, recesses, and more. Enclosures are available with custom colors, while text and graphics can be Laser Screen Printed with pictureperfect quality. Fibox stocks all standard accessories and can quickly install them, giving you a ready-made solution right out of the box.

ARCA accessories

| Back Panel | | | | | | | |
|----------------|------------------------|--------------------------|----------------------------|--|--|--|--|
| Panel Size | Steel Panel Order Code | Plastic Panel Order Code | Aluminium Panel Order Code | | | | |
| 10 x 6 inches | MPS ARCA 3020 | MPSP ARCA 3020 | MPSA ARCA 3020 | | | | |
| 14 x 10 inches | MPS ARCA 4030 | MPSP ARCA 4030 | MPSA ARCA 4030 | | | | |
| 18 x 14 inches | MPS ARCA 5040 | MPSP ARCA 5040 | MPSA ARCA 5040 | | | | |
| 22 x 14 inches | MPS ARCA 6040 | MPSP ARCA 6040 | MPSA ARCA 6040 | | | | |
| 26 x 18 inches | MPS ARCA 7050 | MPSP ARCA 7050 | MPSA ARCA 7050 | | | | |
| 30 x 22 inches | MPS ARCA 8060 | MPSP ARCA 8060 | MPSA ARCA 8060 | | | | |

| Adjustab | le Depth Kits* | DIN Rail Frame Sets* | | Inner Door Sets | |
|---|---|----------------------|-----------------|-----------------|---------------|
| CBS ARCA 15 | Adjust depth of back panel/din rail frame | DRS ARCA 203015 | DRS ARCA 504021 | IDS ARCA 2030 | IDS ARCA 5040 |
| CBS ARCA 21 Adjust depth of back panel/din rail frame | | DRS ARCA 302015 | DRS ARCA 507030 | IDS ARCA 3020 | IDS ARCA 5070 |
| CBS ARCA 30 Adjust depth of back panel/din rail frame | | DRS ARCA 304021 | DRS ARCA 604021 | IDS ARCA 3040 | IDS ARCA 6040 |
| | | DRS ARCA 403015 | DRS ARCA 608030 | IDS ARCA 4030 | IDS ARCA 7050 |
| Wall Mo | ount Lug Sets | DRS ARCA 403021 | DRS ARCA 705030 | IDS ARCA 4050 | IDS ARCA 8060 |
| WMK ARCA 10 | Adds 0.4 inches be- tween wall & cabinet | DRS ARCA 405021 | DRS ARCA 806030 | IDS ARCA 4060 | |
| WMK ARCA 40 Adds 1.6 inches between wall & cabinet | | DRS ARCA 406021 | | | |

^{*} Adjustable Depth Kits included with DIN rail frame sets (DRS)

| Technical Information | | | | | |
|-----------------------------------|----------------|--|--|--|--|
| Property | | Polycarbonate (PC) | | | |
| Environmental | ingress | UL Type 4 and 4X | | | |
| Impact resistar | nce (EN 62262) | IK10 +35°C / IK09 -25°C | | | |
| Temperature R | ange: °Celsius | -40°+140°C | | | |
| Short term | °Fahrenheit | -40°+284°F | | | |
| Temperature R | ange: °Celsius | -40°+80°C | | | |
| Long term | °Fahrenheit | -40°+175°F | | | |
| Electrical insula | ation | Fully insulated | | | |
| Color | | RAL 7035 - Light gray | | | |
| Gasket | | Formed in place polyurethane (PUR) | | | |
| Glow Wire Test Self-extinguish | • | 960° | | | |
| Flammability ra | ating | Enclosure flammability rating per UL 508 | | | |
| Toxicity | | Non-Toxic, halogen free, RoHS compliant | | | |
| UV Resistance | | Complies with UL 508 | | | |
| Chemical Resis | tance | Good | | | |
| | | | | | |

Conformity of Standard N/IEC 62208, EN/IEC 61439-1-4 RoHS directive 2001/65/EU Low-voltage Directive 2006/95/EC (p to 1500 VCD EN 62208:200



Fibox Enclosures 888.342.6987 410.760.9696 www.fiboxusa.com sales@fiboxusa.com